


<i>HEALTH AND SAFETY MANUAL</i>	
Title: Hearing Conservation Program	
Approved by: Greg Savoy	3/4/11

1 Purpose/Scope:

The purpose of this program is to provide a process to minimize employee-hearing loss caused by excessive occupational exposure to noise.

This program is applicable to all employees who may be exposed to noise in excess of 85 decibels (dBA) TWA. When work is performed on a non-owned or operated site, the operator's program shall take precedence, however, this document covers Company employees and contractors and shall be used on owned premises, or when an operator's program doesn't exist or is less stringent.

2 Definitions / Responsibilities:

2.1 Definitions:

2.1.1 Audiometric testing - means detection by the person being tested of a series of pure tones. For each tone, the person indicates the lowest level of intensity that they are able to perceive.

2.1.2 dBA – means the sound energy measured by a sound level meter using the “A” scale.

- The “A” scale is electronically weighted to simulate the response of the human ear to high and low frequency noise.

2.1.3 Slow Response – means the setting on the sound level meter that averages out impulses of brief duration that would cause wide fluctuation in the sound level meter reading.

2.1.4 Standard Threshold Shift – means a change in hearing threshold relative to the baseline audiogram of an average of 10 dB (corrected for age) at 2000, 3000 and 4000 Hz in either ear.

2.2 Responsibilities:

2.2.1 Managers/Supervisors:

- If applicable, ensure requirements of this program are established and maintained.

- Ensure employees are trained and comply with the requirements of this program.

2.2.2 Employees:

- Wear hearing protection when and if required, attend the training, and cooperate with testing and sampling.

3 Requirements:

3.1 General:

3.1.1 Occupational hearing loss is a cumulative result of repeated or continued absorption of sound energy by the ear; employee protection is based on reduction of the noise level at the ear or limiting the employee's exposure time.

- The Company shall offer hearing protection to all employees exposed to potential high noise levels in working areas and to those employees requesting hearing protection.

3.1.2 All employees, who work in areas where the exposure to noise levels are 85 dBA TWA or greater, must wear hearing protection.

3.1.3 For specific noise environments (i.e. extremely high noise areas >100 dba) evaluation of hearing protector attenuation will be required.

3.2 Surveys:

3.2.1 Surveys will be conducted by a qualified employee or third party.

3.2.2 To evaluate noise exposure in terms of possible hearing damage, it is necessary to know the overall sound level ("A" scale measurement), the exposure time of the individual in hours per day and the length of time the individual has worked in the area being surveyed. This data shall be supplemented by the following:

- Name of area and location
- Date and time of survey
- Name of person conducting survey
- Description of instrument used, model and serial number
- Environmental conditions
- Description of people exposed

3.2.3 The company shall notify each employee of their monitoring results, or, if their job is exposed to noise 85 dBA TWA or greater.

3.2.4 All sound measuring equipment must be calibrated before and after each survey. Records of sound measuring equipment calibration and noise level surveys shall be kept for 20 years.

3.2.5 Noise Surveys must be repeated whenever changes in the workplace may expose additional personnel to high noise or hearing protection being used by employees may not be adequate to reduce the noise exposure to a level below 85 dBA TWA.

3.2.6 Sound Level Surveys:

- All owned facilities that are suspected of having noise levels exceeding 85 dBA TWA must be screened.

3.3 Signage:

3.3.1 Clearly worded signs shall be posted at entrances to, or on the periphery of, areas where employees may be exposed to noise levels in excess of 85 dBA. These signs shall describe the hazards involved and the required protective actions.

3.3.2 **NOTE:** Company shall implement this hearing conservation program for employees exposed to sound levels 85dba TWA or grater.

3.4 Audiometric Testing:

3.4.1 Each employee who is exposed to noise 85 dBA (8 hr TWA) or greater must take an audiogram annually.

- An employee must receive a baseline audiogram within six months of their first exposure to 85 dBA TWA or greater for an eight hour period.
- Prior to establishment of a baseline audiogram at least 14 hours without exposure to workplace noise shall be observed.
- An employee shall receive an annual audiogram every year they work in a position that is exposed to noise 85 dBA TWA or greater.

3.4.2 A qualified third party shall perform all employee audiometric testing, evaluations, reporting and retesting.

- Audiometric testing shall be preceded by a period of at least 14 hours during which there is no exposure to workplace sound levels in excess of 80 dBA TWA.
- This requirement may be met by the use of hearing protectors that reduce the employee noise exposure level below 80 dBA TWA.
- An orthoscopic exam is required before an audiogram is initiated. A qualified person shall examine the ear canal for any ear infections or canal irregularities that might affect the audiogram or rule out the use of earplugs.

3.4.3 Annual audiograms shall be evaluated as follows:

- Each annual audiogram shall be compared to the employees' baseline audiogram to ensure the test was valid and to determine if a standard threshold shift has occurred.
- If a standard threshold shift is determined, the employee will be retested within 30 days.
- The retest results will be considered as the annual audiogram.
- In the event of a standard threshold shift occurs employees shall be notified in writing within 21 days of determination.
- If the employee has sustained a standard threshold shift, after re-evaluation, that employee shall be retrained and refitted for appropriate hearing protection.
- The employee shall be referred for additional medical evaluation if indicated.

3.4.4 Employee audiograms are considered medical/exposure records.

- These records must be kept for the length of employment plus 30 years.

3.5 Hearing Protection Devices:

3.5.1 Earmuffs and earplugs shall be made available to the employee in sizes and configurations that will be comfortable to the employee. These hearing protection devices shall be made available to all employees exposed to an 8 hour time-weighted average of 85 db at no cost to employees.

- Employees shall be instructed how to obtain the proper fit.

3.6 Training Program:

3.6.1 A training program shall be established to inform employee, on an annual basis, of the effect of noise on hearing; the purpose of hearing protectors, including the advantages, disadvantages and alternatives of various types, including instructions on selection, fitting, use and care; and the purpose of audiometric testing and an explanation of test procedures.

- The training must be documented.

3.7 Regulation:

3.7.1 A copy of the OSHA "Occupational Noise Exposure" regulation (29 CFR 1910.95) must be made available and accessible to all employees at the Company facility.

- 4 References:
 29 CFR 1910.95, Occupational Noise Exposure.

- 5 Exhibits:
 None.